

The 7000D series drive-up ATMs offer exceptional value and reliable performance. Plus, they feature scalability and adaptability that make them excellent options for maximum revenue.

Features

Easy Installation

Rear- or side-access makes it easier to install these ATMs—whether adding new or replacing out-dated equipment.

Reliability

The Monimax 7000D Series meets demanding performance standards, including UL 291Level 1 vaults, PCI-certified EPP, ADA compliance, and a fully weatherized exterior.

Convenient Options

- 7000D: drive-up with rear access
- 7000DS: drive-up with side access



Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



The Monimax 7000D Series includes two full-service, drive-up models that include state-of-the-art features at a reasonable price.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 7000D

System Control

- Embedded Microsoft® Windows XP® platform
- Intel® Pentium®-IV processor

Customer Display

- 10.4" TFT Color LCD
- SVGA (800 x 600) resolution
- Optional sunlight viewable

Communication

- Dial-up
- TCP/IP (SSL configurable)

Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Supervisor Operation

- 5.7" Mono display
- 4 x 4 numeric keys
- 4 x 2 function keys

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- 2,000-note cassette
- Optional cassettes (up to three)

Printers

- 3.1" graphical thermal receipt printer

Security

- UL291 Level 1 safe
- Electronic safe lock
- Optional KABA Mas Cencon safe lock

Optional Equipment

- Heater
- Envelope depository

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: 20°F–110°F
- With heater: -30°F–110°F
- Humidity: 10%–90%

Dimension and Weight

- Height: 56.3" (1,430 mm)
- Width: 26.7" (678 mm)
- Depth: 27.5" (700 mm)
- Weight: 1,200 lbs (590 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.